



PROSEAL- (ITEM CODE: JAN-201)

HIGH SOLIDS ACRYLIC EMULSION FLOOR SEALER

Proseal is an Acrylic Polymer designed especially for use as a sealer for almost all types of floors, including terrazzo, marble, tiles and concrete.

ADVANTAGES

Its exceptional toughness and non-yellowing characteristics make it unique. **Proseal** has been formulated to make it less sensitive to most strippers, thus allowing Floor Finishes (Polishes), placed over it to be stripped off without affecting the sealer.

INSTRUCTIONS FOR USE

Proseal can be applied over newly laid or existing concrete, terrazzo, marble floors. Floor must be cleaned with light Neutral Cleaner to remove any dust that would prevent sealer from bonding to surface. For existing floors, if any previous treatments have been applied, these must be stripped thoroughly, PROTAIN SPEED STRIPPER can be used. The floor must be cleaned of all chemicals and allowed to dry.

Proseal must be used directly as supplied in accordance with normal janitorial **Proseal PROSEAL** must be used directly as supplied in accordance with normal janitorial practices.

Proseal can be used diluted only as a maintenance measure in the final mop water, one (1) cup **Proseal** to one (1) gallon water.

DISCLAIMER : TO THE BEST OF OUR KNOWLEDGE , THE INFORMATION CONTAINED HEREIN IS ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR THIRD PERSONS CAUSED BY THE MATERIAL IF PROPER SAFETY PROCEDURES ARE NOT ADHERED TO OR IF ABNORMAL USE IS MADE OF THE MATERIAL. IN NO EVENT WILL SELLER BE LIABLE FOR ACCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS MATERIAL

SCL products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms & Conditions of Sale, copies of which may be obtained on request. Whilst SCL endeavors to ensure that any advice, recommendations, specification or information it may give is accurate and correct, it cannot because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

For high traffic areas use of PROGLOSS PREMIUM is recommended as an appropriate finish.

For daily-maintained floors, PROGLOSS REWARD should be used and PROBUFF 123 as a buffing agent.

PROTAIN NC neutral floor cleaner should be used to clean floors on a regular basis as this product would not strip off the floor finishes.

GENERAL PROPERTIES

Appearance	- White Liquid
Odour	- Acrylic
Specific Gravity	- 1.020 -1.030
pH	- 8.0 - 9.0
% Solids	- 16.5 - 18.5

COVERAGE

One (1) gallon per 2000 sq. ft. for single coat
One (1) gallon per 1000 sq. ft. for two coats
Coverage depends on surface absorption.

CAUTION

Keep away from children

OTHER SPECIALIST PRODUCTS INCLUDE

HS-310 LIQUID HAND SOAP

ID-411 LIQUID DETERGENT

PINESPEC PINE DISINFECTANT

Revision #04 Dated: July 11 2023

LP #45 Saddle Road, San Juan, Trinidad & Tobago.
Tel: 1-(868) 675-5555 | Fax: 1-(868) 638-6302 | E-mail: sales@scl-group.com | Website: www.scl-group.com

TRINIDAD | JAMAICA | ST. LUCIA | GUYANA