

# HYDRO TONE



Super Stone® Hydro Tone color stains are a blend of inorganic pigments combined with acrylic copolymers that are designed to produce translucent staining on unsealed Super Surface® and Super Tex® overlay and on porous unsealed concrete.

## RECOMMENDED USAGE

- Unsealed Overlays
- Unsealed Bricks and Pavers
- Unsealed Porous Masonry Surfaces
- Indoor & Outdoor Use

## ADVANTAGES

- Durable & Aesthetically Appealing
- No Odor
- Available in all colors (at the Opa-Locka location only)

## COVERAGE

1 Gallon Covers Approximately 150 ft<sup>2</sup>  
5 Gallons Cover Approximately 750 ft<sup>2</sup>

## DRY TIME

24 hours for foot traffic  
72 hours for vehicular traffic

## SURFACE PREPARATION

Before applying Super Stone® Hydro Tone, make sure all contaminants and bond-inhibiting materials are removed from the surface. Use Super Stone® Cleaner/ Degreaser to remove dirt, oil, and other petroleum based contaminants. Use Super Stone® Strip It Off to remove old acrylics, epoxies, and polyurethanes. Failure to remove contaminants will result in adhesion loss, reduced durability, or peeling. After cleaning, the surface must be allowed to dry completely or moisture may become trapped beneath the sealer resulting in peeling. Concrete must be fully cured.

## APPLICATION

Super Stone® Hydro Tone may be applied with a roller, sponge, brush, quality pump-up sprayer with a fan tip, or an airless sprayer. The appearance of the finish will vary depending upon the application method, dilution rate, and number of applications. Super Hydro Tone colors stains will cover approximately 150 sq. ft. when used at full strength. Coverage rates will vary depending on dilution rate and porosity of surface.

**Coloring:** Super Hydro Tone stains are available in 30 standard colors or a neutral base on the job coloring with Super Stone® Liquid Dispersion Colors. Super Stone can match any color at the Opa-Locka, FL location.

Lighter and darker shades are created by using less/more of Super Stone® Liquid Dispersion Colors and/or water coats. Allow surface to dry completely and coat with one of Super Stone® Clear Sealers when desired effects are achieved.

## APPLICABLE STANDARDS

Resin Type:	Acrylic Copolymer
Solid Content:	15%+3% by weight
Dry time:	30-45 minutes (to touch) 2 hours (to recoat) 12 hours (to seal)
Weight per gallon:	8.5 lbs
60° Specula Gloss:	N/A
VOC:	5g. /L

## LIMITATIONS

Super Stone® Hydro Tone should not be used in areas subject to:

- Water Submersion
  - Significant Chemical Exposure
  - Concentrated Abrasion/Scratching
  - Metal Wheel Traffic
  - Roadways
- or as a waterproofing material or below-grade surfaces such as:
- Swimming Pools
  - Concrete Ponds

It is recommended to test a small area or make color samples to gage color and technique. Color charts associated with Super Hydro Tone are approximate and represent as closely as possible the look of Super Hydro-Tone stains. Variations in shading may occur depending upon job conditions and concrete finish. The end-user assumes full responsibility of coloring and technique. Super Stone® Inc. will not be liable for undesired effects or coloring unless otherwise pertinent to the Limited Manufacturer's Warranty.

## SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended. Avoid breathing vapor for prolonged periods of time and use gloves to avoid repeated contact with the skin. Do not use near fire or flame. Do not smoke during application and drying periods. In case of fire, use CO2 or dry chemical extinguisher. Do not use water spray.

Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes and seek immediate medical attention. **Skin**-- Wash the affected area thoroughly with soap and water. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If symptoms persist or develop, seek medical attention. **Ingestion**-- Do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water. Get medical attention immediately.

**Limited Warranty: Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING**

**THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits.**

FOR PROFESSIONAL USE

**WARNING!** EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. PROLONGED CONTACT AND HIGH CONCENTRATION MAY CAUSE DERMATITIS.

