TECHNICAL DATA SHEET

KONKLEEN- (ITEM CODE: ST-020)

ACID BASED CONCRETE CLEANER, REMOVER AND ETCHING AGENT

Konkleen is a concentrated concrete cleaner that penetrates to break up and dissolve lime deposits, scale, rust, algae and stains. **Konkleen** is used in the scale removing process in sewerage plants, water treatment facilities, etc. It is also useful for the removal of concrete droppings from brickwork and concrete surfaces and safe to use on wood, glass, plastics and rubber.

ADVANTAGES

Saves time – effectively dissolves all films and deposits that would normally require scraping and brushing.
Stains and discoloration disappear with only one application.

INSTRUCTIONS FOR USE

A small trial area should be cleaned first to determine the suitable dilution.

Cleaning Brickwork

Pre-soak brickwork with water. Using a sponge, rub the affected area with a dilution of one part Konkleen to one part Water, according to the severity of the deposits. When the reaction has stopped, wash down area with clean water.

GENERAL PROPERTIES

Appearance:	Light Brown Liquid
Odor:	Acidic
pH (10%)	1.00-2.00

Removing Hardened Concrete From Machinery and Equipment

For large equipment, Ready-mix trucks, concrete barrows, etc. Liberally apply with soft broom to the deposits and leave overnight if possible. Prior cracking of the surface with the deposit will assist penetration and speed up the operation. Considerable deposits may require further treatment with Konkleen. After treatment, dissolved deposits and loose, insoluble materials can be brushed and washed away with clean water.

For small equipment, soak overnight, then wash with clean water. For steel posts and stanchions, etc., dilute one to one with water and pre-soak area, brush clean and rinse with clean water. Repeat if necessary.

Cleaning Floors

Pre-soak floor with water. Using a stiff bristled broom, agitate the affected areas with a dilution of one part Konkleen to one part water, accordingly. When reaction has stopped, wash floor well with clean water.

Removal of Rust and Millscale from Steelwork

Pre-soak equipment with dilution of one part Konkleen to one part Water. Leave to soak until reaction has finished.

CAUTION

Konkleen is an acid based mineral. Keep out of the reach of children. Do not ingest, avoid skin contact. Ensure adequate ventilation. In case of skin contact, wash area immediately with water. If eye contact occurs, wash immediately with water and seek medical attention.
See MSDS for details.

DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR THIRD PERSONS CAUSED BY THIS MATERIAL IF PROPER SAFETY PROCEDURES ARE NOT ADHERED TO OR IF ABNORMAL USE IS MADE OF THE MATERIAL. IN NO EVENT WILL SELLER BE LIABLE FOR ACCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS MATERIAL.

SCL products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms & Conditions of Sale,copies of which may be obtained on request. Whilst SCL endeavors to ensure that any advice ,recommendations,specification or information it may give is accurate and correct,it cannot because it has no direct or continuous control over where or how its products are applied,accept any liability either directly or indirectly arising from the use of its products,whether or not in accordance with any advice,specification,recommendation or information given by it.

Revision 04 Date: January 2023

LP #45 Saddle Road, San Juan, Trinidad & Tobago.
Tel: 1-(868) 675-5555 | Fax: 1-(868) 638-6302 | E-mail: sales@scl-group.com | Website: www.scl-group.com
TRINIDAD | JAMAICA | ST. LUCIA | GUYANA